

# graboflex GYMFIT 60





Property	Standard	Unit	Result
----------	----------	------	--------

DESCRIPTION			
Surface	-	-	PUR Surface
Backing	-	-	Closed cell PVC foam
Thickness	EN ISO 24346	mm	6
Weight	EN ISO 23997	kg/m <sup>2</sup>	3,5
Width	EN ISO 24341	m	2
Standard roll length	EN ISO 24341	m	15 ± 10%
Maximal roll length	EN ISO 24341	m	25

CLASSIFICATION			
Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirements of EN 14904 on sub-construction		
Thermal resistance	-	m <sup>2</sup> K/W	0,05
Reaction to fire	EN 13501	-	C <sub>fl</sub> -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

SPORT PROPERTIES			
Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	18
Ball rebound	EN 12235	%	98
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS			
Dimensional stability	EN ISO 23999	%	± 0,2
Indentation resistance	EN 1516	mm	0,23
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN ISO 26987	-	no change
Abrasion resistance	EN 660-1		T

OTHERS			
Limited warranty			7 years
Cleanability			Easy to clean
Environmental attributes	 		No periodic renewal needed; Solvent and heavy metal free