

## graboflex START

Property	Standard	Unit	Result
----------	----------	------	--------

### DESCRIPTION

Top layer	-	-	PUR Surface
Backing	-	-	Closed cell PVC foam
Thickness	EN ISO 24346	mm	4
Weight	EN ISO 23997	kg/m <sup>2</sup>	2,7
Width	EN ISO 24341	m	2
Standard roll length	EN ISO 24341	m	20 ± 10%
Maximal roll length	EN ISO 24341	m	25

### CLASSIFICATION

Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirements of EN 14904 on sub-construction		
Thermal resistance	-	m <sup>2</sup> K/W	0,03
Reaction to fire	EN 13501	-	C <sub>fl</sub> -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

### SPORT PROPERTIES

Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	9
Vertical deformation	EN 14809	mm	0,4
Ball rebound	EN 12235	%	> 90
Specular gloss	EN 2813	%	< 30

### TECHNICAL CHARACTERISTICS

Dimensional stability	EN ISO 23999	%	± 0,2
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN ISO 26987	-	no change
Abrasion group	EN 660-1		T

### OTHERS

Limited warranty



7 years

Environmental attributes



No periodic renewal needed;  
Solvent and heavy metal free

**GRABOPLAST Floor Covering Manufacturers Ltd.**  
H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100  
mail@graboplast.hu www.graboplast.hu