

REGUPOL®

AKTIVPLUS™

Precision Training Flooring



 REGUPOL

1/2" THICK SYSTEM



Step up to the next level with REGUPOL AktivPlus – 1/2" thick high-density sports flooring. Developed to withstand the abuse of performance training – it is a full 25% thicker for added durability and shock absorption – for the more demanding needs many of the country's student and recreational athletic facilities need, and it's a solid rolled flooring product... virtually seamless when installed. It provides protection to your facility floor and equipment, with budget in mind.


We revolutionized the market again with REGUPOL AktivPlus – educational and performance facilities across North America can train to be the best, while training on the best.




Core Series




AKP10100
Jet Black




AKP10101
Gray Hound



AKP10102
Jayz Blue




AKP10103
Blue Streak



AKP10109
Raging Red


Tone Series



AKP20110
Orange Crush




AKP20111
Green Goblin




AKP20112
Golden Night


Strength Series



AKP35105
Red Devil



AKP35107
Stormy Night



AKP35109
Blue Devil

custom colors

Choose from our wide range of standard colors or invent your own. REGUPOL will combine our own vibrant EPDM color granules to create a custom color that matches your brand standards.



REGUPOL CRASH

Crash is our ultra-dense proprietary surface that is specifically engineered for the “drop-zone” of inlaid platforms, as well as critical areas that require ultra-dense rubber performance surfaces.

branding capabilities

REGUPOL offers solutions for customizing AktivPlus and other products so that your floor plays an active role in the continuity of your brand. Using our precision water-jet cutting, your logo, tagline or inspirational message can be incorporated into your REGUPOL performance floor.

REGUPOL®
AKTIVPLUS™

Product Specifications

Product: Regupol AktivPlus
 Dimensions: 1/2" x 48" wide rolls

Product Performance Data

Force Reduction	ASTM F2772	19.70%
Energy Restitution	ASTM F2772	80.20%
Abrasion Resistance	ASTM D3389	<1.7g, 1000 cycles
Static Load Limit	ASTM F970	0.001" @ 250 PSI
Coefficient of Friction	ASTM D2047	>0.95
Slip Resistance	ASTM F2772	Pass
Pill Test	ASTM D2859	Pass
VOC Compliant	ASTM D5116	Yes
Density	ASTM D3676	60 pcf
Hardness	ASTM D2240 (Shore A)	60 +/- 5
Tear Strength	ASTM D624	80 pli min
Elongation	ASTM D412	>145%
Tensile Strength	ASTM D412	>220 PSI
Flexibility	ASTM F137 1/4" Mandrel	Pass
Resistance to Chemicals	ASTM F925	No Change
VOC Compliant	ASTM D5116 / CA 1350	Yes
LEED Qualification	Qualifies for Material and Resources Credit	
Rolling Load	EN1569	Pass
Resistance to Impact	EN1517	14 N/m
Resistance to Indentation	EN1516	0.1mm
Vertical Deformation	ASTM F2772	1.4mm
Environmental Product Declaration	ISO14025	-101047-4150



Please feel free to contact us:
 Phone+1 800.537.8737
 Email sales@regupol.com